




DIMENSIONES MÁXIMAS

F-195
S-220

S-220 AF
F-250 E
F-275 E

F-250 I
F-275 I
F-300 E
F-300 I
F-330 I
F-350



DIMENSIONES MÁXIMAS Y PESOS

MODELO	F-195	S-220	S-220 AF	F-250 E	F-250 I	F-275 E	F-275 I	F-300 E	F-300 I	F-330 I	F-350 I
COTA A (mm)	255	280	280	290	340	290	340	340	410	410	415
COTA B (mm)	345	415	415	440	465	440	465	465	530	530	580
COTA C (mm)	360	405	405	425	480	440	495	495	540	550	585
COTA D (mm)	310	540	540	610	630	620	640	650	770	760	890
COTA E (mm)	315	320	335	365	445	390	430	400	460	465	480
PESO (kg)	10	13,5	13,5	15	21	16,5	21	23	30	32	36

DATOS TÉCNICOS PRINCIPALES

MODELO	F-195	S-220	S-220 AF	F-250 E	F-250 I	F-275 E	F-275 I	F-300 E	F-300 I	F-330 I	F-350 I
Diámetro cuchilla (mm)	195	220	220	250	250	275	275	300	300	330	350
Revoluciones cuchilla (rev/min)	300	300	300	300	300	300	300	300	280	280	260
Corte útil (mm)	160 x 140	210 x 160	210 x 160	240 x 190	260 x 190	240 x 190	260 x 190	260 x 220	285 x 230	285 x 250	325 x 260
Espesor corte (mm)	0-15	0-15	0-15	0-16	0-16	0-16	0-16	0-16	0-16	0-16	0-16
Servicio	Intermitente (5 minutos de descanso cada 15-20 minutos de funcionamiento)										
Motor monofásico (HP) 220V-240V 50/60 Hz	0,20	0,25	0,25	0,30	0,35	0,30	0,35	0,35	0,50	0,50	0,50